



Clinical, pharmaceutical and research laboratories require laboratory grade distilled water or equivalent quality water that consistently meets stringent water standards. Water below a desired quality not only affects the chemistry of the test conducted but also damages the instruments, which in turn, reduces the reliability of the test and also increases calibration time and reagent cost.

Ion Exchange with over five decades of experience in innovative total water management solutions presents INDION Lab-Q Water Maker. It is easy to install and has several built-in safety features for reliable and consistent water supply of purified laboratory grade water.

Features

- Online Conductivity Meter - Displays product water quality for continuous monitoring
- Automatic Flush Device (AFD) - Ensures periodic cleaning of the system
- Dry Run Protection - Ensures protection of the pump when inlet water is unavailable
- Optional Filtration - Can be attached at the point of dispensing spout to ensure compliance to microbial reduction values
- Spare Kit - Lab-Q Guard and Lab-Q Clear are included to avoid downtime
- Instant water dispensing with single touch user interface

Advantages

- Provides an efficient alternative to buying and storing laboratory grade distilled water
- Compact and portable counter top model ensures optimal use of space
- Low operating cost
- Requires minimum maintenance

Applications

- Accessory for random access auto analyzers
- For reagent preparations and washing
- Instrument analysis
- Pharmaceutical industry
- Heating baths and biomedical applications
- Water for inverter batteries



Feed Water Specification

| Parameters | Limits |
|----------------------------|--|
| TDS | 500 ppm max. |
| Turbidity | 5 NTU |
| Iron / Magnesium | Nil |
| Oil & Grease | Nil |
| Free Chlorine | Nil |
| Silica | <20 ppm |
| Inlet Pressure | Min 0.5 kg/cm ² Max 2.0 kg/cm ² |
| Total Organic Carbon (TOC) | 3 ppm |

Performance Parameters

| Parameters | Limits |
|----------------------------|------------------------------|
| Capacity | 10 l/h |
| Turbidity | <1 NTU |
| Conductivity | <1 $\mu\text{S}/\text{cm}^2$ |
| Total Organic Carbon (TOC) | <200 ppb |

Product Specifications

| Parameters | Limits |
|-------------------|--------------------------|
| Dimensions | 450 mm x 240 mm x 440 mm |
| Weight | 13 kg |
| Power Requirement | 230 V AC \pm 10% |
| Power Consumption | 40 watts |

To the best of our knowledge the information contained in this publication is accurate. Ion Exchange (India) Ltd. maintains a policy of continuous development and reserves the right to amend the information given herein without notice. Please contact our regional / branch offices for current product specifications.

INDION is the registered trademark of Ion Exchange (India) Ltd.

ION EXCHANGE (INDIA) LTD.

Corporate Office

Ion House, Dr. E. Moses Road,
Mahalaxmi, Mumbai 400 011
Tel: +91 22 3989 0909 | Fax: +91 22 2493 8737
E-mail: ieil@ionexchange.co.in

International Division

R -14, T.T.C MIDC, Thane - Belapur Road,
Rabale, Navi Mumbai 400 701
Tel: +91 22 3989 0909 / 3913 2400 | Fax: +91 22 2769 7918
E-mail: export.sales@ionexchange.co.in

OFFICES

| Regional | Telephone | Fax | E-mail |
|---------------|------------------------------|------------------|-------------------------------|
| Chennai | +91 44 3989 0909 / 3910 2900 | +91 44 2815 3361 | checro@ionexchange.co.in |
| Delhi | +91 11 3989 0909 / 3054 3200 | +91 11 2577 4837 | delcro@ionexchange.co.in |
| Kolkata | +91 33 3989 0909 / 3043 3400 | +91 33 2400 4345 | calcro@ionexchange.co.in |
| Vashi | +91 22 3989 0909 / 3913 2300 | +91 22 2788 9839 | mumcro@ionexchange.co.in |
| Branch | | | |
| Bengaluru | +91 80 2204 2888 | +91 80 2853 2002 | bngcro@ionexchange.co.in |
| Bhubaneswar | +91 674 326 9525 / 257 1491 | | bbsr@ionexchange.co.in |
| Chandigarh | +91 172 274 5011 | +91 172 274 4594 | delcro@ionexchange.co.in |
| Hyderabad | +91 40 3066 3101 / 02 / 03 | +91 40 3066 3104 | hydrcro@ionexchange.co.in |
| Lucknow | +91 522 319 9911 | +91 11 2577 4837 | lko.general@ionexchange.co.in |
| Vadodara | +91 265 302 7489 / 90 | +91 265 2352 932 | brdcro@ionexchange.co.in |
| Visakhapatnam | +91 891 324 6253 | | sales.vizag@ionexchange.co.in |

Factories: Ankleshwar | Hosur | Patancheru | Rabale | Verna

All India Service and Dealer Network

www.ionindia.com